

## Monsoon Compact Plate Fans

- Die cast aluminium blade & external rotor motor design
- Motors dynamically balanced to ISO 1940 & IP54 protected
- Motor insulation Class F
- Temperature operation -40° to +70°
- Thermal overload for motor protection
- Terminal box IP54 protection



### Single Phase 4 Pole

CODE	DESCRIPTION
EQ-25-WA	250mm (756m <sup>3</sup> /h)
EQ-31-2A	315mm (2,052m <sup>3</sup> /h)
EQ-35-2C	355mm (3,456m <sup>3</sup> /h)
EQ-40-4C	400mm (5,040m <sup>3</sup> /h)
EQ-45-4C	450mm (6,192m <sup>3</sup> /h)
EQ-50-4F	500mm (7,560m <sup>3</sup> /h)
EQ-56-6K	560mm (13,932m <sup>3</sup> /h)
EQ-63-6N	630mm (18,324m <sup>3</sup> /h)

### Three Phase 4 Pole

CODE	DESCRIPTION
DQ-31-2A	315mm (2,088m <sup>3</sup> /h)
DQ-35-2C	355mm (3,600m <sup>3</sup> /h)
DQ-40-2F	400mm (5,328m <sup>3</sup> /h)
DQ-45-4C	450mm (6,480m <sup>3</sup> /h)
DQ-50-4F	500mm (8,172m <sup>3</sup> /h)
DQ-56-6F	560mm (12,348m <sup>3</sup> /h)
DQ-63-6K	630mm (18,684m <sup>3</sup> /h)