

Manufacturers & suppliers of monsoon products

Shower Extract Kit Range



- High performance and low power consumption
 - Up to 198m³/h
 - As low as 17-19W
- Quick and easy installation
- Made in the UK
- Runs at 28dB(A) on low speed
- Shower grille

- Two speed motor with option of overrun timer (2 to 30 minutes)
- Motor equipped with Standard Thermal Overload Protection
- IPX4 rated
- Voltage 220-240V 50Hz
- Premium build quality

Call now to find out more: 01823 690 290


www.nationalventilation.co.uk Email: info@nvagroup.co.uk

CODE	DESCRIPTION
UMDTK	Kit includes UMD100T, 2x internal diffuser (white and chrome), 6m PVC flexible ducting, external fixed grille and 4x cable ties

CODE	DESCRIPTION
	Kit includes UMD100T, cool white LED light, 2x air diffuser (white and chrome), 6m PVC flexible ducting, external fixed grille and 4x cable ties

The UMD Domestic range can be used for exhaust and supply ventilation systems that require high pressure, powerful airflow and low noise levels. The UMD range can be used with rigid and flexible ducting, and are the ideal solution for air exhaust systems for rooms with high humidity such as bathrooms and kitchens. For larger sizes (125 - 200), please see the UMD Pro range.


Performance



Technical data

	UMD100	
	HIGH	LOW
Power (W)	19	17
Current (A)	0.1	0.09
Maximum air flow (m ³ /h)	198	155
Sound @ 3m dB(A)	32	28
Rotation speed (min ⁻¹)	1710	1460

Dimensions (mm)



Call now to find out more: 01823 690 290

www.nationalventilation.co.uk Email: info@nvagroup.co.uk