

Manufacturers & suppliers of monsoon products

Monsoon Shuttered Fan Range



- Simple installation
- External 2 speed reversible on/ off controller available
- Manufactured impact resistant high gloss ABS for strength and durability
- Motor fitted with thermal over load protection

- Meets the requirements of Building Regulation Document F
- IP44 rated, DEMKO Approved, and CE marked in accordance with all the relevant EEC Harmonised Directives
- Double Insulated, class II motor fitted with thermal protection

Call now to find out more: 01823 690 290 www.nationalventilation.co.uk Email: info@nvagroup.co.uk

9" & 12" Auto Shutter Fan

CODE	DESCRIPTION
MON23A	225mm Auto Shutter - 190l/s
MON30A	300mm Auto Shutter - 267l/s

23/30 Controllers & Accessories

CODE	DESCRIPTION
MON23WK	230mm Window Kit to suit
MON30WK	300mm Window Kit to suit
MONRS23/30	2 speed reversible on/off controller

Fixed grilled fan suitable for panel/wall mounting or window mounting using the appropriate window accessory kit. Suitable for commercial applications in pubs, hotels, restaurants, offices, schools, shops and factories.

This is one of the most popular wall/panel extractors we offer, suitable for commercial and semi-domestic use.

Technical Specification

Meets the requirement of Building Regulation Document F. IP44 Rated DEMKO Approved CE marked in accordance with all the relevant EEC Harmonised Directives Rated Voltage 220-240V 50Hz Double Insulated Class II

Performance

Model:	MON30A	MON23A
Airflow I/s:	267	190
Extract Noise dbA (@3m):	51.3	52.4
Intake Noise dbA (@3m):	50.1	52.3
Rated wattage Watts:	100	90
-		

Dimensions (mm)

Model:	MON30A	MON23A
Grille height:	403	340
Grille width:	403	340
Wall model hole dia.:	337	280
Wall model max wall thickness:	305	305
No. of wall tube segments:	17	14
Window model hole dia.:	337	260
Window model glass thickness:	5 - 32	5 - 32
Number of window kit fasteners:	4	3

Call now to find out more: 01823 690 290

www.nationalventilation.co.uk Email: info@nvagroup.co.uk